



467126EX

TAIS-EX SWITCHED SOCKET IN THERMOSETTING (GRP) WITH MECHANICAL INTERLOCK 16A
2P+E 200-250V 50-60HZ 6H 2D 3G



Registry		Technical data	
Net weight	2,8	Dimensions	125X380X160 mm
Min order quantity	1	Hole type	M25
EAN Code	8014950051793	Frequency	50-60Hz
Reference Standards	Directive	Protection level	IP66
EN 60079-0/A11: 2013	2014/34/EU	Poles	2P+ $\frac{1}{2}$
EN 60079-0: 2012	2014/35/EU	Clock Position	6
EN 60079-15: 2010		Nominal Operating Voltage	230V
EN 60079-31: 2014		Manufacturing Material	Thermosetting halogen free
EN 60309-1/A1: 2007		Width	125 mm
EN 60309-1/A1EC: 2014		Nominal current	16A
EN 60309-1/A2: 2012		Execution	WALL MOUNTING
EN 60309-1: 1999		Protection	none
EN 60309-2/A1: 2007		Insulation Class	II
EN 60309-2/A2: 2012		Atex	
EN 60309-2: 1999		ATEX application zone	Zona/Zone 2, 21 and 22
EN 60309-4/A1: 2012		Notified body (CE)	 0051
EN 60309-4: 2007		Certificate Number IECEx	IECEx EXA 15.0004X
Marks		Atex Dust Nominal Current	16
		Atex Gas Nominal Current	16
		Atex Dust Marking	Ex tb IIIC T90/T105°C Db
		Atex Gas Marking	Ex nR IIC T6/T5 Gc
		Certificate Number ATEX	TÜV IT 13 ATEX 049 X
		GAS Dissipable Power	-
		DUST Dissipable Power	-
		Min. Amb. Temp.	-40°C
		Max. Amb. Temp.	+50°C/+65°C
		T Cable °C	95
		Temp. amb. max. 2	+65°C
		Group & Cat. ATEX GAS	II 3G
		Group & Cat. ATEX DUST	II 2D